


DS-2CE56C0T-VPIR


HD720P Vandal Proof IR Dome Camera



Key features

- 1.0 Megapixel high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night, Smart IR
- Up to 20m IR distance
- Vandal proof

Dimensions



Accessories



Available models

DS-2CE56C0T-VPIR

DS-2CE56C0T-VPIR	
Camera	
Image Sensor	1 MP CMOS Image Sensor
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.1 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm optional)
	Angle of View: 70.9°(3.6mm), 92°(2.8mm), 56.7°(6mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Turbo HD output
General	
Working Temperature/ Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 4W
IR Range	Up to 20m
Impact Protection	IK10
Dimension	Φ 111 × 82.4(Φ 4.37" × 3.24")
Weight(approx.)	550g (1.21 lbs)